




PER.	Capacity Kg	Shaft-W (A)	Shaft-D (B)	Car-W (C)	Car-D (D)
3	225	1500	1500	800	900
4	300	1550	1550	850	1050
5	375	1700	1700	1000	1100
6	450	1800	1800	1100	1150
8	600	1800	1800	1100	1400
10	750	1900	1900	1200	1550
12	900	2000	2000	1300	1650
15	1125	2000	2000	1300	2000
20	1600	2100	2100	1400	2400

PIT : 1200 mm • O .H. : 3660 mm




PER.	Capacity Kg	Shaft-W (A)	Shaft-D (B)	Car-W (C)	Car-D (D)
10	750	1900	1950	1200	1550
12	900	2000	2050	1300	1650
15	1125	2000	2400	1300	2000
18	1350	2050	2650	1350	2250
20	1500	2100	2800	1400	2400
26	2000	2300	3000	1600	2600
33	1700	2500	3200	1700	2800
40	3000	2700	3400	1900	3000

PIT : 1500 mm • O .H. : 3900 mm





PER.	Capacity Kg	Shaft-W (A)	Shaft-D (B)	Car-W (C)	Car-D (D)
10	750	1900	1950	1200	1550
12	900	2000	2050	1300	1650
15	1125	2000	2400	1300	2000
18	1350	2050	2650	1350	2250
20	1500	2100	2800	1400	2400
26	2000	2300	3000	1600	2600
30	2300	2400	3100	1700	2700
33	2500	2500	3200	1700	2800

PIT : 1500 mm • O .H. : 3900 mm



Person	Capacity Kg	Shaft-W (A)	Shaft-D (B)	Car-W (C)	Car-D (D)
3	225	1200	1200	800	900
4	300	1250	1350	850	1050
5	375	1400	1400	1000	1100
6	450	1500	1500	1100	1150
8	600	1500	1700	1100	1400
10	750	1600	1850	1200	1550
12	900	1700	1950	1300	1650
15	1125	1700	2300	1300	2000
20	1500	1800	2700	1400	2400
24	1800	1900	2800	1500	2500

PIT : 1500 mm • O .H. : 3900 mm  
(PIT & O.H. change the technical specification)



**PASSENGER LIFT**

Capacity Person	Lift Speed Kgs. Mtr./Sec.	Lift Well A	Lift Well B	Cabin Inside C	Cabin Inside D	Entry E
5	340 0.35 / 0.50	1650	1500	1220	780	700
6	408 0.35 / 0.50	1650	1550	1220	930	700
5	340 0.35 / 0.50	1800	1600	1170	830	800
6	408 0.35 / 0.50	1800	1550	1370	830	800
8	544 0.35 / 0.50	1800	1750	1420	1030	800
10	680 0.35 / 0.50	1850	1900	1220	1480	800

PIT : 1200mm # OVER HEAD : 3660 mm


**STRETCHER CUM PASSENGER LIFT**

13	884 0.35 / 0.50	1800	2500	1070	2080	800
16	1088 0.35 / 0.50	2000	2700	1070	2230	900
20	1360 0.35 / 0.50	2000	3000	1270	2480	900
13	884 0.35 / 0.50	2000	2500	1070	2080	900
16	1088 0.35 / 0.50	2250	2700	1120	2230	1000
20	1360 0.35 / 0.50	2250	3000	1270	2480	1000

PIT : 1200mm # OVER HEAD : 3660 mm



**TELESCOPIC AUTO DOOR**



**PASSENGER LIFT**


Capacity Person	Lift Speed Kgs. Mtr./Sec.	Lift Well A	Lift Well B	Cabin Inside C	Cabin Inside D	Entry E
5	340 0.35 / 0.50	1400	1700	1070	900	700
6	408 0.35 / 0.50	1450	1800	1120	1000	700
5	340 0.35 / 0.50	1550	1550	920	1050	800
6	408 0.35 / 0.50	1550	1700	920	1200	800
8	544 0.35 / 0.50	1650	1900	1020	1400	800
10	680 0.35 / 0.50	1650	2250	1020	1750	800

PIT : 1200mm # OVER HEAD : 3660 mm

**STRETCHER CUM PASSENGER LIFT**


13	884 0.35 / 0.50	1700	2900	1020	2400	800
16	1088 0.35 / 0.50	1800	2900	1070	2400	900
20	1360 0.35 / 0.50	1900	3000	1270	2500	1000

PIT : 1200mm # OVER HEAD : 3660 mm



PER.	Capacity Kg	Shaft-W (A)	Shaft-D (B)	Car-W (C)	Car-D (D)
3	225	1300	1300	800	900
4	300	1350	1450	850	1050
5	375	1500	1500	950	1100
6	450	1600	1550	1050	1150
8	600	1600	1800	1200	1300
10	750	1700	1950	1200	1550
12	900	1800	2050	1300	1650
15	1125	1800	2400	1350	2000
20	1600	1900	2800	1500	2400

PIT : 1200 mm • O .H. : 3660 mm



PER.	Capacity Kg	Shaft-W (A)	Shaft-D (B)	Car-W (C)	Car-D (D)
10	750	1900	1950	1200	1550
12	900	2000	2050	1300	1650
15	1125	2000	2400	1300	2000
18	1350	2050	2650	1350	2250
20	1500	2100	2800	1400	2400
26	2000	2300	3000	1600	2600
30	2300	2400	3100	1700	2700
33	2500	2500	3200	1700	2800

PIT : 1500 mm • O .H. : 3900 mm